

Aggregation Switch

HSP-IO-24GE4XS-C2A+

24-Port Non PoE L2 Managed Switch
(24x1G Access + 4x1/10G SFP+ Uplinks)



Overview

- Fully Managed L3 Lite Switch with wire speed Non-Blocking Architecture
- All Gigabit Ethernet Access Ports with 10G Uplinks in a fixed 1U configuration
- 24x10/100/1000 Base-T Access ports
- 4x1/10G SFP+ Uplink Ports that allow termination on either fiber or copper based on SFP module
- Powerful WebGUI with DMS and automapping feature
- Upto 128 Gbps Switching capacity and up to 95.232 MPPS of Full Duplex Throughput
- Comply with Energy Efficient Ethernet Standards (802.3az)
- Non-PoE Variants Suitable as access or aggregation switch in Enterprise/ Campus/ Telco Environment

Switch Ports

- 24x10/100/1000 Base-T Gigabit Access Ports
- 4x1/10G SFP+ Uplink Ports (MSA Compliant) with the flexibility to terminate the connection on copper or fiber-based SFP module
- One Serial Console Port
- Link / Speed / LED Status on All ports
- System status LED

Industry Standard Management with Automation

- CLI and WebGUI
- Dual Stack (IPv4 and IPv6) Management
- Telnet, SSHv2 and SNMP v1/v2/v3, RMON and sFlow
- NTP, FTP, TFTP, SCP, SFTP, Port Mirroring, Traceroute
- DHCP Server, Relay and Client
- TDR (Time domain reflectometry) for cable diagnostics
- Zero Touch Provisioning

HSP-IO-24GE4XS-C2A+

KEY FEATURE HIGHLIGHTS



Rich L2 Features

- Support 4094 VLAN IDs, 32K MAC Table, Voice VLAN, IPsubnet VLAN, Protocol VLAN, Private VLAN, MAC based VLAN, MVRP
- L2 Loop Avoidance – STP/RSTP, MSTP, STP Root and Edge Port Protection, Loop back detection, UDLD
- Multicast - IGMP v1/v2/v3 Snooping, IGMP filtering, IGMP proxy, MLD Snooping, MVR
- LACP based LAG and Static LAG with Traffic load share and active –standby policies
- 802.1q and QinQ (Port based)
- QoS – Up to eight priority queues, Rate Limiting/ Policing, Shaping (SP, WRR), Multi-Field (802.1p / DSCP) Classification and Remarking
- LLDP / LLDP MED to identify end points, IP Phones etc.
- Jumbo MTU upto 10240 Bytes

L3 Features

- IPv4 and IPv6 Static Routing
- RIP v1/v2 L3 Dynamic Routing
- OSPFv2/v3 L3 Dynamic Routing
- Inter-VLAN Routing
- IPv4/IPv6 Dual Stack

Power Supply Options

- Integrated Single AC Power Supply (100-240 VAC)

Security Features

- L2/L3/L4 ACL with extended features
- 802.1X Port Security with Radius Accounting & Dynamic VLAN Assignment
- TACACS+ / RADIUS AAA
- DHCP snooping, Dynamic ARP Inspection
- Port Security, Sticky MAC, IP-MAC Binding
- PKI Key, Certificate
- Storm Control - Broadcast, Multicast and Unknown Unicast

Design Parameters

- Operating Temperature: -5°C to 50°C
- 1U fixed configuration
- Humidity: 10% to 90% non-condensing
- Altitude: 3000 Meters (10,000 Feet)
- Dimension (WxHxD): 442 x 44 x 211 mm

Switching / Forwarding Capacity

Switching Capacity 128 Gbps

Forwarding Capacity 95.232 MPPS

Ordering Information

Model No.	Description
HSP-IO-24GE4XS-C2A+	IO, 24-Port, Non PoE, L2 Managed Switch, 4x1/10G SFP+ Uplinks, Single AC Power Supply
HSP-IO-Cable-AC-IN	AC Power Cable, 1.5M (India Plug)

Disclaimer: HFCL, IO by HFCL, and their respective logos are trademarks and/or registered trademarks of HFCL Limited. HFCL Limited assumes no responsibility for any inaccuracies in this document and reserves the right to revise or transfer this document without notice. All other trademarks, service marks, registered marks, or registered service marks mentioned herein are the property of their respective owners.

Last Updated September 06, 2024



Email: iosupport@hfcl.com

Website: hfcl.com | io.hfcl.com

Office: 8, Commercial Complex, Masjid Moth, Greater Kailash II, New Delhi 110048